

Larsen Building Products Ltd

n55Plus



Professional Flexible Standard Set Adhesive

By Larsen Building Products Ltd

Detailed description

Specially formulated, polymer modified, deformable, standard setting, cement based adhesive. Suitable for beds of 3–6 mm (12 mm maximum in isolated areas), interior, exterior, floor and wall applications. Can be used in areas which are totally immersed in water, e.g. swimming pools and wet rooms.

Suitable for:

- Ceramic, marble/ natural stone, porcelain, glass, mosaic and terrazzo tiles.
- Under floor heating and over sheeted timber.
- Grouting after 24 hours.

Product guidance - As Standard

Features:

- Form: Powder.
- Mix: 20 kg powder: 5 L water.
- Application temperature: + 5–30°C.
- Light traffic: 24 hours.
- Coverage: 6–7 m²/ 20 kg bag @ 3 mm bed.
- Tensile adhesion strength: ³ 1 MPa.

Options

Primer:

Gypsum screeds and plaster one coat diluted 1:1 with water followed by one coat neat, porous substrates one coat diluted 1:1 with clean water.

Product specification

Manufacturer

- Name: Larsen Building Products Ltd
- Web: www.larsenbuildingproducts.com
- Email: joris@larsenbuildingproducts.com

Product reference Professional Flexible Standard Set Adhesive

Colour Grey
White

Primer

None
Larsen Acrylic primer