

Larsen Building Products Ltd

NS Plus



## Professional SLC 2000 Industrial By Larsen Building Products Ltd

### Detailed description

Fast drying, hand or pump applied cement based levelling screed for the renovation of concrete floors. Manufactured from a controlled blend of special sands, cements and synthetic polymers to give a high quality flooring product which is self-levelling and smoothing. For use in fast track commercial and industrial situations where a wearing finish is required or when finishes need to be applied quickly. It is ideal for warehouses, production areas and similar areas where a hardwearing level finish is required.

### Product guidance - As Standard

Features:

- Form: Granular.
- Colour: Grey.
- Aggregate size (maximum): 1.2 mm.
- Bed thickness: 5–30 mm.
- Mix: 25 kg powder: 5 L water.
- Application temperature: + 5–30°C.
- Light traffic: 2–4 hours.
- Full traffic: 1–2 days.
- Coverage: 1.25 m<sup>2</sup> per 25 kg @ 10 mm.
- Screed compressive strength: 35 MPa.

### Options

Primer:

- Larprime EU Epoxy: For heavy traffic areas.
- Larsen acrylic: For light traffic areas.

### Product specification

Manufacturer

- Name: Larsen Building Products Ltd

- Web: [www.larsenbuildingproducts.com](http://www.larsenbuildingproducts.com)  
- Email: [joris@larsenbuildingproducts.com](mailto:joris@larsenbuildingproducts.com)

Product reference Professional SLC 2000 Industrial

Primer Not required  
Larprime EU Epoxy  
Larsen acrylic primer diluted 1:1 with clean water - Normal concrete/ screed.  
Larsen acrylic primer diluted 1:1 with clean water followed by a coat of neat acrylic primer - Particularly porous concrete/ screed.